

To
Kingston K-14 School District
Leta Lute
10047 Diamond Road
Cadet, Mo 63630
573-438-4982 892 (Contact)

ITEM 1 - DISHWASHER, CONVEYOR TYPE (1 REQ'D)

Hobart Model CL44EN-BAS+BUILDUP Dimensions: 68.5(h) x 44.75(w) x 31.25(d)

Conveyor Dishwasher, single tank, (202) racks/hour, insulated hinged doors, .62 gallon/rack, stainless steel enclosure panels, microprocessor controls with low temperature & dirty water indicators, NSF Pot & Pan mode, programable de-lime notification, ENERGY STAR®, Free factory startup for installations within a 100 mile radius of a Hobart service office; installation beyond 100 miles will be charged at the quoted rate by the local Hobart service office



- 1 ea Standard warranty - 1-Year parts, labor & travel time during normal working hours within the USA
- 1 ea Model CL44EN-BASHT15K Electric tank heat 15kW
- 1 ea Model CL44EN-BASERH30K 30kW electric booster
- 1 ea Dual Point (2) service connection standard
- 1 ea Model CL44EN-BASELE0AB 200v/50/3-ph
- 1 ea Model CL44EN-BASHGTSTD Standard height
- 1 ea Model CL44EN-BASDIR0LR Left to right operation
- 1 ea Model CL44EN-BASFETSTD Standard feet
- 1 ea Model WS80-NOINSTALL Water softening system 4,818 grains/lb capacity, 14 gallons regeneration volume, salt alarm, holds 2 bags of salt, pricing DOES NOT include installation. INSTALLATION BY AUTHORIZED HOBART SERVICE OFFICE IS RECOMMENDED (NET)
- 2 ea Model VNTHD/E-ADJ E-series vent hood domestic (adjustable)
- 1 ea Model CLE/TBL-SWITCH Table limit switch CLE-Series
- 1 ea Accurex Model XCUE-099-VG Exhaust Fan and GPI -19-12-G14 Roof Curb.

Installer to provide duct from machine to fan.

ITEM 2 - HAND SINK (1 REQ'D)

Advance Tabco Model 7-PS-EC-X Dimensions: 13(h) x 18(w) x 16(d)

Special Value Hand Sink, wall mounted, 14" wide x 10" front-to-back x 5" deep bowl, 304 stainless steel construction, splash mounted faucet, 1-1/2" basket drain, wall bracket, NSF



ITEM 3 - WIRE SHELVING (5 REQ'D)**Olympic Model J2436K Dimensions: 36(w) x 24(d)**

Shelf, wire, 24" x 36", green epoxy finish with chromate substrate, NSF

- 5 ea 1 year warranty against manufacturing defects
- 5 ea 7 year warranty against rust and corrosion
- 4 ea Model J86K Post 86", stationary, grooved at 1" intervals, includes leveling bolt & cap, green epoxy finish with chromate substrate, NSF

**ITEM 4 - WIRE SHELVING (5 REQ'D)****Olympic Model J2442K Dimensions: 42(w) x 24(d)**

Shelf, wire, 24" x 42", green epoxy finish with chromate substrate, NSF

- 5 ea 1 year warranty against manufacturing defects
- 5 ea 7 year warranty against rust and corrosion
- 4 ea Model J86K Post 86", stationary, grooved at 1" intervals, includes leveling bolt & cap, green epoxy finish with chromate substrate, NSF

**ITEM 5 - HOSE REEL (1 REQ'D)****T&S Brass Model B-7102-01M-STB**

Hose Reel Assembly, open, 3/8" x 12' with 1.15 GPM spray valve (B-0107), adjustable hose bumper, table leg mounted swing bracket, includes mounting hardware, 3/8" NPT female inlet, stainless steel

- 1 ea 1 year limited warranty for hose, standard
- 1 ea 2 year limited warranty for hose reel, standard

**ITEM 6 - PRE-RINSE FAUCET ASSEMBLY (1 REQ'D)****T&S Brass Model B-0133-12CRBJST**

EasyInstall Pre-Rinse Unit, 8" wall mount, add on faucet 12" swivel nozzle, Cerama cartridges with check valves, lever handles, 18" riser, 44" flexible stainless steel hose, 1.07 GPM, accessory fitting, wall bracket, low lead, NSF (B-0230-K)

**ITEM 7 - PRE-RINSE FAUCET ASSEMBLY (1 REQ'D)****T&S Brass Model B-5125-CR-B8P**

EasyInstall Workboard Pull-Down Pre-Rinse Unit, wall mount mixing faucet, 8" center, spring action gooseneck, 1.15 GPM spray valve, 12" riser, 30" flexible stainless steel hose, 6" wall bracket, 1/2" NPT male inlet, lever handles, quarter-turn Cerama cartridges, low lead, 2019 DOE PRSV - Class II

**ITEM 8 - WALL / SPLASH MOUNT FAUCET (2 REQ'D)****T&S Brass Model B-0231-CR-KIT**

Pantry Faucet, double, wall mount, 8" centers, 12" swing nozzle, lever handles, stream regulator tip, quarter-turn Cerama cartridge, low lead, (2) 24" flex hose, 1/2" NPT, NSF, ADA Compliant



ITEM 9 - DRAIN, LEVER / TWIST WASTE (3 REQ'D)**T&S Brass Model B-3950**

Waste Valve, twist handle, 3-1/2" sink opening, 2" drain outlet with 1-1/2" adapter (replaces B-3912, B-3916)

**ITEM 10 - SERVICE FAUCET (1 REQ'D)****T&S Brass Model B-0665-CR-BSTRK**

Service Sink Faucet, wall mount, mixing faucet with 8" adjustable centers, Cerama cartridges with check valve, lever handles with color coded indexes, upper support bracket, vacuum breaker spout, built-in stops, chrome plated brass body, 1/2" NPT female inlets, low lead, cCSAus, ADA Compliant (B-0230-K)

1 ea 1 year limited warranty, standard

**ITEM 11 - MOP SINK (1 REQ'D)****Advance Tabco Model 9-OP-28 Dimensions: 10(h) x 33(w) x 25(d)**

Mop Sink, floor mounted, 33"W x 25"D x 10"H (overall), 28"W x 20" front-to-back x 6" deep (bowl size), free flow drain with 2" IPS outlet, stainless steel construction, NSF

1 ea Model K-242 Mop Hanger, 23", accommodates (3)

**ITEM 12 - SHELVING, WALL MOUNTED (1 REQ'D)****Advance Tabco Model WS-12-36-X Dimensions: 10.5(h) x 36(w) x 12(d)**

Special Value Shelf, wall-mounted, 36"W x 12"D, 1-5/8" bullnose front edge, 1-1/2"H rear up-turn, 18/430 satin finish stainless steel, NSF

**ITEM 13 - WIRE SHELVING (5 REQ'D)****Olympic Model J2448K Dimensions: 48(w) x 24(d)**

Shelf, wire, 24" x 48", green epoxy finish with chromate substrate, NSF

5 ea 1 year warranty against manufacturing defects

5 ea 7 year warranty against rust and corrosion

4 ea Model J86K Post 86", stationary, grooved at 1" intervals, includes leveling bolt & cap, green epoxy finish with chromate substrate, NSF

**ITEM 14 - WALL GRID SHELVING UNIT (3 REQ'D)****Metro Model SWK36-1A1-SR Dimensions: 31(h) x 40(w) x 40(d)**

POS Sink Task Station Wall Shelving Kit, includes: (1 each) 40" wall track, 18" x 36" Metroseal 3™ wire shelf & wire grid, wire basket, lid holder, utensil cylinder & cylinder holder (2 each) uprights, shelf supports & prong hooks (6) standard hooks, 400 lb. capacity per unit

**ITEM 15 - CUSTOM SOILED DISHTABLE (1 REQ'D)****SPG International Model CUSTOM**

"L" SHAPED SOILED DISHTABLE, 115"X 102-1/2"X30" WIDE, 16 GA. S/S TOP WITH 9" SPLASH, S/S LEGS AND CROSSRAILS WITH ADJUSTABLE BULLET FEET.

1 ea Model DTO-5 Universal Stainless Pre-rinse Sink Bowl, 20" x 20" x 6" (offered in 14 or 16 gauge, please specify when ordering)

5 ft Model DTO-14 Universal Stainless Pass through Window Ledge, per linear foot

1 ea Model NO FAUCETS FAUCETS NOT INCLUDED.

ITEM 16 - CUSTOM CLEAN DISHTABLE (1 REQ'D)

SPG International Model CUSTOM

STRAIGHT CLEAN DISHTABLE, 94" LONG X 30" WIDE, 16 GA. S/S TOP WITH 9" SPLASH, S/S LEGS AND CROSSRAILS WITH ADJUSTABLE BULLET FEET.

1 ea Model SO-10 Universal Stainless End Splash Standard Height 9"

ITEM 17 - CUSTOM 3 COMP SINK (1 REQ'D)

SPG International Model CUSTOM

STRAIGHT THREE COMPARTMENT SINK, 149" LONG X 28" WIDE, 16 GA. S/S TOP WITH 9" SPLASH, S/S LEGS AND CROSSRAILS WITH ADJUSTABLE BULLET FEET.

- 1 ea Model SO-5-CN Universal Stainless Disposal Cone Weldment (Cone by Others)
- 1 ea Model SO-7 Universal Stainless Vacuum Breaker Holes, set
- 1 ea Model SO-9-C Universal Stainless Disposer Control Bracket, 12" x 16"
- 3 ea Model SB-282012 Universal Stainless Weld-In Sink, one compartment, 28" x 22" x 12", NSF
- 1 ea Model SO-10 Universal Stainless End Splash Standard Height 9"
- 1 ea Model NO FAUCETS FAUCETS NOT INCLUDED.

ITEM 19 - DISPOSER (1 REQ'D)

Salvajor Model 100-SA-3-MRSS

Disposer, Sink Assembly, 3-1/2" sink collar, 1 Hp motor, start/stop push button manual reversing MRSS control, includes fixed nozzle, chrome plated vacuum breaker, solenoid valve, sink stopper & flow control, heat treated aluminum alloy housing, UL, CSA, CE (**Effective 6-1-17 all MRSS control panel dimensions will be 9-1/4" x 10-1/4" x 5-7/16"**))

- 1 ea 208v/60/1-ph, 10.2 amps
- 1 ea Model 980104 Mounting bracket for RSS, MSS, MSS-LD, MRSS, MRSS-LD



ITEM 20 - DISPOSER (1 REQ'D)

Salvajor Model 100-CA-12-MRSS

Disposer, 12" cone assembly, 1 Hp motor, start/stop push button manual reversing MRSS control, includes fixed nozzle, chrome plated vacuum breaker, solenoid valve, scrap ring & flow control, 6-1/2" inlet diameter, heat treated aluminum alloy housing, UL, CSA, CE (**Effective 6-1-17 all MRSS control panel dimensions will be 9-1/4" x 10-1/4" x 5-7/16"**))

- 1 ea 208v/60/1-ph, 10.2 amps

